



**SAFETY DATA SHEET**  
CONTRACTOR FUSION - ALL COLOURS

Page 1  
Issued: 27/04/2010  
Revision No: 1

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

**Product name:** CONTRACTOR FUSION - ALL COLOURS  
**Product code:** 44080 - 44085  
**Company name:** ROCOL  
ROCOL House  
Swillington  
Leeds  
West Yorkshire  
LS26 8BS  
ENGLAND  
Tel: +44 (0) 113 232 2700  
Fax: +44 (0) 113 232 2740  
Emergency tel: +44 (0) 113 232 2600  
Email: [customer-service@rocol.com](mailto:customer-service@rocol.com)

## 2. HAZARDS IDENTIFICATION

**Main hazards:** Extremely flammable. Vapours may cause drowsiness and dizziness.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

**Hazardous ingredients:** HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE) 10-30%  
EINECS: 270-704-2 CAS: 68476-85-7  
[F+] R12

- XYLENE 10-30%  
EINECS: 215-535-7 CAS: 1330-20-7  
[-] R10; [Xn] R20/21; [Xi] R38
- ACETONE 10-30%  
EINECS: 200-662-2 CAS: 67-64-1  
[F] R11; [Xi] R36; [-] R66; [-] R67
- 1-METHOXY-2-PROPANOL 5-10%  
EINECS: 203-539-1 CAS: 107-98-2  
[-] R10; [-] R67

## 4. FIRST AID MEASURES (SYMPTOMS)

**Skin contact:** There may be irritation and redness at the site of contact.  
**Eye contact:** There may be irritation and redness. The eyes may water profusely.  
**Ingestion:** There may be soreness and redness of the mouth and throat.  
**Inhalation:** There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.

## 4. FIRST AID MEASURES (ACTION)

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.  
**Eye contact:** Bathe the eye with running water for 15 minutes. Obtain medical attention if soreness or redness persists.  
**Ingestion:** Wash out mouth with water. Consult a doctor.  
**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. Seek medical attention if you feel unwell.

## 5. FIRE-FIGHTING MEASURES

**Extinguishing media:** Carbon dioxide. Dry chemical powder. Use water spray to cool containers.  
**Exposure hazards:** In combustion emits toxic fumes.  
**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

[cont...]

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

**Environmental precautions:** Do not discharge into drains or rivers.

**Clean-up procedures:** Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space.

**Storage conditions:** Store in cool, well ventilated area. Keep away from sources of ignition.

**Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** HYDROCARBON AEROSOL PROPELLANT (<0.1% 1,3-BUTADIENE)  
WEL (8 hr TWA): 1000ppm 1750mg/m<sup>3</sup> WEL (15 min STEL): 1250ppm 2180mg/m<sup>3</sup>

- XYLENE

WEL (8 hr TWA): 220 mg/m<sup>3</sup> WEL (15 min STEL): 441 mg/m<sup>3</sup>

- ACETONE

WEL (8 hr TWA): 1210 mg/m<sup>3</sup> WEL (15 min STEL): 3620 mg/m<sup>3</sup>

- 1-METHOXY-2-PROPANOL

WEL (8 hr TWA): 375 mg/m<sup>3</sup> WEL (15 min STEL): 560 mg/m<sup>3</sup>

**Engineering measures:** Ensure there is sufficient ventilation of the area.

**Respiratory protection:** Respiratory protection not normally required in well ventilated area. If workplace exposure limits are exceeded respiratory protection may be required. Gas/vapour filter, type A: organic vapours (EN141).

**Hand protection:** Gloves (solvent-resistant).

**Eye protection:** Safety glasses with side-shields.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Aerosol

**Colour:** Various

**Odour:** Characteristic odour

**Evaporation rate:** Fast

**Solubility in water:** Slightly soluble

**Flash point°C:** -30

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat. Sources of ignition.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Hazardous ingredients:** XYLENE  
ORL MUS LD50 2119 mg/kg  
ORL RAT LD50 4300 mg/kg  
SCU RAT LD50 1700 mg/kg

- ACETONE  
IVN RAT LD50 5500 mg/kg  
ORL MUS LD50 3 gm/kg  
ORL RAT LD50 5800 mg/kg
- 1-METHOXY-2-PROPANOL  
IVN RAT LD50 4200 mg/kg  
ORL MUS LD50 11700 mg/kg  
ORL RAT LDLO 3739 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

## 12. ECOLOGICAL INFORMATION

**Bioaccumulative potential:** No data available.

**Other adverse effects:** No data available.

## 13. DISPOSAL CONSIDERATIONS

**Disposal operations:** Incineration, landfill, observe local regulations

**Waste code number:** 140603

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

## 14. TRANSPORT INFORMATION

### ADR / RID

**UN no:** 1950

**ADR Class:** 2

**Classification code:** 5F

**Shipping name:** AEROSOLS

**Labelling:** 2.1



### IMDG / IMO

**UN no:** 1950

**Class:** 2

**EmS:** F-D,S-U

**Labelling:** 2.1

### IATA / ICAO

**UN no:** 1950

**Class:** 2

**Labelling:** 2.1

## 15. REGULATORY INFORMATION

**Hazard symbols:** Extremely flammable.



**Risk phrases:** R12: Extremely flammable.

R67: Vapours may cause drowsiness and dizziness.

**Safety phrases:** S16: Keep away from sources of ignition - No smoking.

S23: Do not breathe spray.

S51: Use only in well-ventilated areas.

S26: In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

S35: This material and its container must be disposed of in a safe way.

**Precautionary phrases:** Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

**Water hazard class:** 2

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 16. OTHER INFORMATION

**Other information:** EC Directive 1999/45/EC relating to the classification, packaging and labelling of dangerous preparations.  
EC Directive 91/155/EEC defining the laying down and detailed arrangements for the system of specific information relating to dangerous preparations.  
EC Directive 94/1/EC adapting some technicalities of Council Directive 75/324/EEC on the approximation of the laws of Member States relating to aerosol dispensers.

**Risk phrases used in s.3:** R12: Extremely flammable.  
R10: Flammable.  
R20/21: Harmful by inhalation and in contact with skin.  
R38: Irritating to skin.  
R11: Highly flammable.  
R36: Irritating to eyes.  
R66: Repeated exposure may cause skin dryness or cracking.  
R67: Vapours may cause drowsiness and dizziness.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.